



SoloPanel® SPI is an innovative photovoltaic module based upon Copper, Indium, Gallium, Selenium ("CIGS") semiconductor material electro-deposited on a flexible stainless steel substrate and encapsulated in a state-of-the-art moisture barrier laminate. It is designed for a wide range of applications.



SoloPanel® Model

SPI

LOW INSTALLED SYSTEM COST

The flexible, lightweight form factor of the SPI enables rapid and easy installation as well as low cost system integration with a wide variety of mounting solutions. The SPI module is optimized for residential and standing seam metal roof integration.

HIGH ENERGY PERFORMANCE

SoloPower® is the market leader in high efficiency flexible modules. Modules are designed for superior performance under all light conditions, including low sun angle, providing excellent energy yield throughout the year.

PROVEN DURABILITY

SoloPower® modules are built to meet or exceed UL 1703, IEC 61646 & IEC 61730 standards. Cells and modules are continually subjected to rigorous environmental and accelerated life cycle testing beyond industry standards.

KEY FEATURES

- + Sixty (60) series connected, high efficiency, CIGS solar cells optimize panel performance
- + Low weight, non-penetrating mounting solutions take advantage of the lightweight module characteristics
- + Superior low-sun angle and low light performance provide excellent energy yield
- + Low profile bypass diodes allow for maximum performance under shade conditions
- + Weather resistant front sheet, sealed junction box and protective back sheet provide a long life, reliable and durable package
- + Modules are built to meet and/or exceed UL standard 1703, IEC 61646 & IEC 61730 standards
- + Manufactured in a highly automated state-of-the-art facility
- + 5-year limited warranty against defective materials and workmanship
- + 25-year warranty on power output
- + Designed and manufactured in USA
- + For a complete listing of SoloPower products visit: www.solopower.com

Imagine Integration

SoloPower, Inc. is a US based manufacturer of high-efficiency thin-film photovoltaic modules based on Copper Indium Gallium di Selenide (CIGS). The unique manufacturing process utilizes a low cost, proprietary electro-deposition tool set. The company is headquartered in San Jose, California.



APPLICATIONS

Segments: Commercial, Industrial, and Residential Rooftops

ELECTRICAL CHARACTERISTICS (STC)¹

Solopower SPI		75	80	85	90	95
Rated Power (Pmax) ²	W	75	80	85	90	95
Voltage at Pmax (Vmp)	V	21.8	22.7	23.3	24.7	26.2
Current at Pmax (Imp)	A	3.4	3.5	3.6	3.6	3.6
Short-circuit current (Isc)	A	4.3	4.3	4.4	4.3	4.2
Open-circuit Voltage (Voc)	V	30.6	31.8	32.4	33.6	34.8
Efficiency ³	%	9.9	10.5	11.2	11.9	12.5

- STC standard test conditions: 1000W/m² intensity, Air Mass 1.5, 25°C cell temperature. The power tolerance is -3% / +5% Wp, at STC. The electrical characteristics are within ± 10% unless otherwise specified.
- Stabilized Power.
- Aperture Efficiency.

Solopower SPI					
Temp. Co-efficient of Isc	%/°C	- 0.03	Pmp	- 0.48	%/°C
Temp. Co-efficient of Voc	%/°C	- 0.36			
Max. Series Fuse Rating	A	7			
Maximum DC Voltage					
US	VDC	600			
EU	VDC	1,000			
NOCT	°C	48			

PHYSICAL CHARACTERISTICS

Solopower SPI		
Length		86.5 in / 2.197 m
Width		15.7 in / 0.398 m
Thickness		0.1 in / 2.0 mm
Weight		4.6 lbs / 2.1 kg
Roof Load From Module		0.49 lbs/ft ² / 2.4 kg/m ²

QUALIFICATIONS

Certified to Standards: UL 1703, IEC 61646, & IEC 61730.




WARRANTY

Limited Warranty
Materials and workmanship: 5 years. Power output: 25 years (90% of nominal rated power for years 1 to 10, 80% of nominal rated power for years 11 to 25). Designed and manufactured in the US.

Contact sales@solopower.com for complete terms of the limited warranty.


©2012 SoloPower, Inc.® All rights reserved. SoloPower®, the SoloPower® logo, and Solo Panel® are trademarks of SoloPower, Inc.® in the US and other countries.

IV CURVES



Current (A) vs. Voltage (V) at various Irradiance levels

MECHANICAL DRAWING



5981 Optical Court
San Jose, CA USA 95138
408-281-1582